

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



# LISTING SERVICE

**LISTING No.** 7165-0410:0159

Page 1 of 2

**CATEGORY:** 7165 -- FIRE ALARM CONTROL UNIT (COMMERCIAL)

**LISTEE:** Hochiki America Corporation 7051 Village Drive, Suite 100, Buena Park, CA 90621-2268  
Contact: Michael Um (714) 670-3248 Fax (714) 522-2268  
Email: mum@hochiki.com

**DESIGN:** Model FireNet 4127 Analog Addressable fire alarm control unit. Automatic, manual, waterflow and sprinkler supervisory service. Refer to the listee's data sheet for detailed product description and operational considerations. System components:

<u>MODULE</u>	<u>PART NO.</u>	<u>DESCRIPTION</u>
FN-4127-BO	(K6002)	Control Board
FN-4127-IO	(K6006)	16 Channel Input/Output Board
FN-4127-CPA-BO	(K6001)	Front LCD Indicator Panel
FN-4127-SLC	(K6004)	Loop 3, 4 Board
FN-4127-NIC	(K6005)	Network Card
FN-PS402	(S402)	Power Supply
FN-DAC	(FN-DAC)	Digital Alarm Communicator
FN-ENC	(FN-ENC)	Enclosures
FN-ACC	(FN-ACC)	Battery/Accessory Enclosure
FN-CTM	(7000-00780)	City Tie Module
D9068	(D9068)	Bosch Digital Alarm Communication Transmitter
HMX-DP		Voice Evacuation System Distribution Panel
HMX-MP		Voice Evacuation System Master Panel
EVX-100		Audio Adjunct Module
EVX-RM		Remote Microphone

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes & ordinances, and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee's name, model number, electrical rating, and UL label.

**APPROVAL:** Listed as fire alarm control unit for use with separately listed compatible initiating and indicating devices. \*Also suitable for high-rise applications.

These control units can generate the distinctive three-pulse Temporal Pattern Fire Alarm Evacuation Signal as required per NFPA 72, 2002 Edition.

This control unit meets the requirements of UL-864, \*9th Edition Standard

**NOTE:** 1. For Fire Alarm Verification Feature (Delay of fire alarm), the maximum

\*Rev 6-24-2009 fm



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2011**

Listing Expires **June 30, 2012**

Authorized By: **FRANCIS MATEO, Program Coordinator**  
Fire Engineering Division

Retard/Reset/Restart period must be adjusted to 30 seconds or less.

2. Combined with 7170-0410:170

\*Rev 6-24-2009 fm



---

This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2011**

*Listing Expires* **June 30, 2012**

Authorized By: **FRANCIS MATEO**, Program Coordinator  
*Fire Engineering Division*