

HCP-202 FIRE ALARM CONTROL PANEL



STANDARD FEATURES

- 2 Class B (Style B) initiating circuits which may be configured as 1 Class A (Style D) circuits
- 2 Class A/B (Style Z/Y) indicating circuits with individual trouble indicators (1.25 Amps max. per circuit)
- Each indicating circuit can be configured as silenceable or non-silenceable. Audibles may be configured as Steady, Temporal Code, California Code or March Time
- Selectable alarm verification on initiating circuits
- Output for 4-wire resettable regulated smoke power supply of 24 VDC 100mA maximum
- Output for RTI or Remote Annunciators of 24VDC, 300 mA max, unfiltered
- Built-in walk test operation
- Auxiliary relay contacts for common alarm, common trouble and common supervisory. If no supervisory circuits are enabled, the supervisory relay becomes a second alarm relay
- 2.75 Amp power supply
- Easy configuration via DIP switches

SPECIFICATIONS	
Primary Input Power	120 volts, 60 Hz, 1 Amps (Optional 220VAC)
Indicating Current	24VDC unfiltered, 2.5Amps
Standby Power	24VDC standby batteries
Charging Capability	4 – 6.5 AH batteries
Dimensions	12 3/4"H x 13 3/4"W x 3 1/8"D

Specifications subject to change without notice.

DESCRIPTION

Hochiki's HCP-202 Fire Alarm Control Panel is a microprocessor based unit designed for small to medium commercial, institutional and industrial occupancies. Fully configurable using DIP switches, it enables the user to configure the system to meet their specific requirements.

The HCP-202 comes standard with 2 Class B (Style B) initiating circuits which may be configured as 1 Class A (Style D) circuits. In addition it comes equipped with 2 Class A/B (Style Z/Y) indicating circuits which are each rated at 1.25 amps. The panel also includes a 2.75 amp power supply which powers the system and supplies a 4-wire resettable regulated smoke power supply of 24 VDC 100mA maximum.

The HCP-202 utilizes a simple DIP switch configuration for programming initiating and indicating circuits as well as the enabling and disabling of system functions such as signal silence, fire drill and auxiliary disconnect. In addition the HCP-202 allows for alarm verification on the initiating circuits. The indicating circuits may be configured as silenceable or non-silenceable with the audibles configured for Steady, March-Time, Temporal Code, or California Code.

The cabinet is available in a beige color for the Canadian market and a red exterior for the U.S. and International markets. A Fire Retardant Lexan Window in the hinged door allows for viewing of the status LEDs. It comes with a durable CAT-30 lock and key. Space is provided for up to 10 AH batteries.



Continued on back.

ORDERING INFORMATION

Model	Description
HCP-202	Fire Alarm Control Panel Two Zone Microprocessor Based Fire Alarm Control Panel comes with 2 Class B (Style B) or 1 Class A (Style D) initiating circuits, 2 Class A/B (Style Z/Y) indicating circuits and a 2.75 amp power supply. Allows for one HDACT-100 Digital Communicator or one HPR-100 Polarity Reversal Module or one HRM-204 or HRM-208 Auxiliary Relay Module. Red enclosure comes with keylock door.
HRTI-1	Remote Trouble Indicator
HDACT-100	Adder Modules Digital Alarm Communication Transmitter/Dialer Module
HPR-100	Polarity Reversal/City Tie Module
HRM-204	Auxiliary Relay Module comes with 4 configurable relays
HRM-208	Auxiliary Relay Module comes with 8 configurable relays <i>(Note: Only one of the above modules can be used with the HCP-202)</i>